

com virtuemart

0



Guarantee 2 year send factory Product
characteristics Suitable for ponds up to 60 m³
Elimination of suspended algae (green water)
Reduction of harmful bacteria and pathogen levels
UVC radiation is at its best at all times thanks to patented, autonomous bulb cleaning Bypass technology enables optimal irradiation of the polluted water, even at high flow through rates Individual water flow adjustment for optimal adaptation to the connected filter pump Integrated magnets protect the UVC technology against limescale deposits Visual function check of the UVC bulb 100 %, VDE-certified safety; does not cause eye injuries Quick release technology for easy bulb replacement High quality workmanship with impact resistant plastic housing Incl. high quality UVC bulb Including OASE Clear Water Guarantee in conjunction with the OASE flow through filters, BioSmart, BioTec and ProfiClear

Dimensions (L x W x H) (mm)	600 x 180 x 198
Rated voltage	220 - 240 V / 50/60 Hz
Power consumption	55 W
Power cable length (m)	5,00
Net weight (kg)	4,52
Guarantee	2 years
UVC power	55 W
Temperature display	No
Bypass control	manually
UVC operating hours meter	No
Number of inlets (EA)	1
Connections, inlet (mm)	19/25/32/38/50
Connections, inlet	¾", 1", 1¼", 1½", 2"
Number of outlets (EA)	2
Connections, outlet (mm)	25/32/38
Connections, outlet	1", 1¼", 1½"
Min. flow rate (l/h)	8000

