

seasunaquarium.com

SeaSun aquarium



Search by Brand



zzz>>>>> Oase

Oase (UVC Sterilizer) Bitron C 110w (110000 liters)
Oase (UVC Sterilizer) Bitron C 72w (75000 liters) Oase (UVC Sterilizer) Vitronic 11w (6000 liters)

Brand:(Oase)



185			
cartAdd			
com	virtuemart		
4			



effectively fight algae with intelligent UVC technology. Pathogens and bacteria are safely reduced through the UVC radiation.

All Bitron devices have well-designed bypass technology. This allows individual adjustment of the water flow which is routed over the UVC bulb via the throttle handle. This makes it possible to set the optimal flow rate. Whether swimming pond, garden biotope, or fish and koi pond â€" Bitron devices are an ideal fit for any pond. Algae, fish waste, and other pond pollutants can reduce the UVC radiation. The unique and integrated cleaning mechanism of the Bitron C range ensures simple, fast, and permanent cleaning of the UVC light source. This guarantees your customers the sustainable effect of the UVC radiation â€" for untroubled satisfaction. ntegrated magnets protect the system from dangerous lime deposits. Lime that is in the water can assume a crystalline form under the thermal development of the UVC light. These aggressive lime structures can destroy the bulb or block the rotor in the pump. The permanent magnets of the OASE Bitron clarifier prevent these crystals from forming through magnetic treatment of the water. This protects the pond as well as the filtration system and guarantees the unusually long service life of the OASE components. All Bitron range UVC clarifiers are equipped with an indicator light or a control window. Thus the function of the UVC bulb can be checked at any time. The light tubes should be changed after every 10,000 mension spine matrion (Lix Mynth) antee 7/34 fx 1/2 \$6 en 2/01 capacity of the UVC light wave \(\forall \). Ottage itron devices have 0 & 40 de/stipe 60 litzaccordance with the **Indetespsecially adapter**. This has **2/4**0 been confirmed by the German VDE, Outlitet has tested and applioned Albe device. With the performa Oppertation of fierd is lator UVC clarifiers text by lating busible component in

Dimensions in mm (LxWxH) 731 x 216 x 201
The product advantages: All UVC clarifiers have an automatic cleaning Voltage 20-240 V/50-60 HZ
system, which ensures that the full output of the light is effectively used.
Inlet special adapter 3/4"-2"
Unique combination of UVC light and permanent magnets (except Bitron Outlet: 2x

9C/11C). The permanent magnet prevents the calcification of important Control Window pump and filter parts (except Bitron 9C/11C). The UVC light flocculates Connection to Biotec 5-36 + Proficiear green algae thus facilitating the filtering process and destroying pathogens.

Pump performance max. (I/h)
Visual function control. Bitron C devices are available in 8 variants (Bitron Power consumption (watt) 110
9C/11C/18C/24C/36C/55C/72C/110C). They are easy to mount on the Through flow UVC without bypass 12000 I/h
Proficiear modular filter and on the Biotec filters
Cable length

Guarantee

2 year

Customer Reviews	:		
here are yet no re Please log in to writ	riews for this product. e a review.		
/ou may also h	n interested in this/these produc	ct(s)	
rou may also b	e interested in this/these produc	Ci(S)	
	Vendor Info	<u>ormation</u>	